



## SG-Ultra Digital Hydrometer/Density Unit



SG-Ultra

### Product Overview

The SG-Ultra digital hydrometer/density meter offers 99.999% accurate, temperature-compensated specific gravity, density, and density-related values. Select from multiple units of measure to suit your measurement needs or create custom user-defined requirements. Results include sample identification, measurement unit, temperature correction coefficient, instrument identification and date & time. Results can be downloaded to a printer or PC easily. Reliable results appear in just 3 seconds - just immerse the sampling tube, pull the trigger, and read the final result. Trend results with included management software. The SG-Ultra is commonly used for battery testing (lead-acid & Ni-cad), alcohol and food testing, petroleum testing, and other custom density tests.

### Advantages

- Accurate 99.999% Accurate
- User-Friendly Compact, lightweight, and allows for one-hand measurement. Large LCD display screen with back-light
- Robust & rugged, comes with protective carrying case. Sustains tough field environments with a sealed housing
- Wireless Communication Infrared data interface for data exchange with a PC and data export to a printer (data transfer accessories included)
- Storage of up to 1100 results including sample ID, measurement unit, temperature correction coefficient, instrument identification, date and time
- The following measuring units are available for selection: Density, Comp. Density, SG (T/T), SG, API, Brix, Alcohol, H2SO4, Baume, Plato, Proof, Concentration
- Reliable CE Compliant and One Year Warranty

### Technical Specifications

<b>Measurement Range:</b>	Density: 0.000 – 2.000 g/cm <sup>3</sup> Sample Temperature: 0 <sup>1</sup> – 40 °C (32 <sup>1</sup> – 104 °F) Viscosity: 0 – 2,000 mPa
<b>Accuracy:</b>	Density: 0.001 g/cm <sup>3</sup> Temperature: ±0.2 °C (±0.4 °F)
<b>Resolution:</b>	0.0001 g/cm <sup>3</sup>
<b>Minimum Sample Volume:</b>	2 mL
<b>Communication:</b>	IrDA Interface
<b>Display:</b>	Backlit LCD
<b>Internal Storage:</b>	1100 Results
<b>Operating Environment:</b>	10 – 50 °C (-15 – 122 °F)
<b>Power Requirements:</b>	(2) AAA Batteries
<b>Dimensions:</b>	229 x 114 x 64 mm (9 x 4.5 x 2.5 in)
<b>Weight:</b>	360 g (2.7 oz)
<b>Sample Tube Dimensions:</b>	142.875 x 3.175 mm / 5.625 x 1/8 in. Diameter *Custom lengths available

(1) Sample must not freeze in the measuring cell



SG-Ultra Kit

### Kit Includes

- SG-Ultra
- Sample Tube (5.625" x 1/8")
- IrDA Adapters
- SG-Ultra Management Software
- Carrying Case
- User Manual

### Ordering Information

Model No.	Description
SG-Ultra	Digital Hydrometer, Data-Logging, Range: 0.0000 – 2.0000